

MATERIAL SAFETY DATA SHEET

POLY ACRYL PA 77

Revision date:

Revision NO: 0

Edition Date:

02/2010

Page:

1/5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

Trade name : POLY ACRYL PA 77

Company : No:771,zereshki alley tajbakhsh street , 25 km karaj special road
,Tehran-Iran

Telephone : (+98 263) 6102231-2 , (+98 263) 6102299

Telefax : : (+98 263) 6102023

Email address : info@awachimie.com

Use of the Substance : It is used in exterior and interior paints.

- PHYSICAL AND CHEMICAL PROPERTIES

Physical state liquid

Colour milky

Odour faint

Total solid (ASTM D 2369) 50±1%

Viscosity (23°C, Brookfield RV #2/RPM 20) 50 - 400 cps

pH (ASTM D 1293) 8.5-9.5

MFFT (ISO 2811) 16°C

Density (ASTM D1475) 1/04-1/1g/cm³

Water solubility dilutable

- FIRST AID MEASURES

General advice

Remove contaminated or saturated clothing.

Skin contact

Wash off with plenty of water and soap immediately.

Eye contact

Rinse with plenty of water immediately, seek medical advice if necessary.

Ingestion.

Seek medical advice.

- HANDLING AND STORAGE

Handling**Safe handling advice**

Avoid contact with skin and eyes.

Application, processing: Provide good ventilation or extraction.

Advice on protection against fire and explosion

Normal measures for preventive fire protection.

Storage**Requirements for storage areas and containers**

Keep container tightly closed.

Protect from frost.

- OTHER INFORMATION

NOTICE: Awa chimie believes the information contained here is accurate. However, Awa chimie makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. , Awa chimie assumes no responsibility for injury from the use of the product described herein.