

TDS OF Poly Acryl SA 400

- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

Trade name	: Poly Acryl SA 400
Company	: No:771,zereshki alley tajbakhsh street , 25 km karaj special road ,Tehran-Iran
Telephone	: (+98 263) 6102231-2 , (+98 263) 6102299
Telefax	: : (+98 263) 6102023
Email address	: info@awachimie.com
Use of the Substance	: It is Mainly used to modify hydraulic binders , to manufacture flexible coatings and as binder in concrete

- PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Colour	milky
Odour	faint
Total solid (ASTM D 2369)	57±1%
Viscosity (23°C, Brookfield RV # 4/RPM 10)	60-140P
pH (ASTM D 1293)	7-9
MFFT (ISO 2811)	< 0°C
Density (ASTM D1475)	1/02-1.08g/cm ³
Water solubility	dilutable

- FIRST AID MEASURES

General advice

Remove contaminated or saturated clothing.

Skin contact

Wash off with plenty of water and soap immediately.

Eye contact

Rinse with plenty of water immediately, seek medical advice if necessary.

Ingestion.

Seek medical advice.

- HANDLING AND STORAGE

Handling

Safe handling advice

Avoid contact with skin and eyes.

Application, processing: Provide good ventilation or extraction.

Advice on protection against fire and explosion

Normal measures for preventive fire protection.

Storage

Requirements for storage areas and containers

Keep container tightly closed.

Protect from frost.

- OTHER INFORMATION

NOTICE: Awa chimie believes the information contained here is accurate. However, Awa chimie makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. , Awa chimie assumes no responsibility for injury from the use of the product described herein.